

Poster presentation

Open Access

## PhAST: pharmacophore alignment search tool

V Hähnke\*, B Hofmann, E Proschak, D Steinhilber and G Schneider

Address: Johann Wolfgang Goethe-University, Beilstein Endowed Chair for Chem-and Bioinformatics, Institut für Organische Chemie und Chemische Biologie, Siesmayerstr 70, D-60323 Frankfurt am Main, Germany

\* Corresponding author

from 4th German Conference on Chemoinformatics  
Goslar, Germany. 9–11 November 2008

Published: 5 June 2009

Chemistry Central Journal 2009, 3(Suppl 1):P67 doi:10.1186/1752-153X-3-S1-P67

This abstract is available from: <http://www.journal.chemistrycentral.com/content/3/S1/P67>

© 2009 Hähnke et al; licensee BioMed Central Ltd.

We developed the Pharmacophore Alignment Search Tool (PhAST), a text-based technique for rapid hit and lead structure searching in large compound databases. For each molecule, a two-dimensional graph of potential pharmacophoric points (PPPs) is created, which has an identical topology as the original molecule with implicit hydrogen atoms. Each vertex is coloured by a symbol representing the corresponding PPP. The vertices of the graph are canonically labelled [1]. The symbols associated with the vertices are combined to a so-called *PhAST-Sequence* beginning with the vertex with the lowest canonical label. Due to the canonical labelling the created PhAST-Sequence is characteristic for each molecule.

For similarity assessment, PhAST-Sequences are compared using the sequence identity in their global pairwise alignment [2]. The alignment score lies between 0 (no similarity) and 1 (identical PhAST-Sequences). In order to use global pairwise sequence alignment, a score matrix for pharmacophoric symbols was developed and gap penalties were optimized. PhAST performed comparably and sometimes superior to other similarity search tools (CATS2D [3], MOE pharmacophore quadruples [4]) in retrospective virtual screenings using the COBRA [5] collection of drugs and lead structures. Most importantly, the PhAST alignment technique allows for the computation of significance estimates that help prioritize a virtual hit list.

### References

1. Weininger D, et al.: *J Chem Inf Comput Sci* 1989, **29**:97.
2. Needleman S, Wunsch C: *J Mol Biol* 1970, **48**:443.
3. Schneider G, et al.: *Angew Chem Int Ed* 1999, **38**:2894.

4. Sheridan RP, et al.: *J Chem Inf Comput Sci* 1996, **36**:128.
5. Schneider P, Schneider G: *QSAR Comb Sci* 2003, **22**:713.