

RESEARCH ARTICLE

Open Access

Detection of stanozolol in environmental waters using liquid chromatography tandem mass spectrometry

Nawed IK Deshmukh^{1*}, James Barker¹, Andrea Petroczi² and Declan P Naughton²

Abstract

Background: Owing to frequent administration of a wide range of pharmaceutical products, various environmental waters have been found to be contaminated with pharmacologically active substances. For example, stanozolol, a synthetic anabolic steroid, is frequently misused for performance enhancement as well as for illegal growth promoting purposes in veterinary practice. Previously we reported stanozolol in hair samples collected from subjects living in Budapest. For this reason we initiated this study to explore possible environmental sources of steroid contamination. The aim of this study was to develop a method to monitor stanozolol in aqueous matrices using liquid chromatography tandem mass spectrometry (LC-MS/MS).

Results: Liquid-liquid extraction using pentane was found to be an efficient method for the extraction of stanozolol from water samples. This was followed by direct detection using LC-MS/MS. The method was capable of detecting 0.25 pg/mL stanozolol when only 5 mL water was processed in the presence of stanozolol D3 as internal standard. Fifteen bottled waters analysed were found to be negative for stanozolol. However, three out of six samples from the Danube river, collected from December '09 to November '10, were found to contain stanozolol at concentrations up to 1.82 pg/mL. In contrast, only one sample (out of six) of urban tap water from Budapest city was found to contain stanozolol, at a concentration of 1.19 pg/mL.

Conclusion: The method developed is efficient, rapid, reproducible, sensitive and robust for the detection of stanozolol in aqueous matrices.

Background

Regular and widespread use of pharmaceuticals, which are frequently excreted as non-metabolized parent compounds, has led to growing concerns for the safety of drinking water [1]. The vast range of pharmaceutical products that have been detected in sewage, surface, ground and drinking waters include bronchodilators, oral contraceptives, antidepressants, beta-blockers, antibiotics, anti-inflammatories and analgesics [2-7]. Even modern sewage treatment works are not constructed to specifically eliminate pharmaceuticals [1] from potable water supplies.

Stanozolol, an anabolic steroid is a synthetic derivative of the endogenously-produced male-sex hormone testosterone. It is commonly misused as a performance

enhancement drug because of its ability to enhance muscular strength. The World Anti-Doping Agency (WADA) has banned its use in- and out-of-competition [8]. Despite the restriction, stanozolol is one of the most commonly misused synthetic, anabolic steroids in sport [9] and in veterinary practice, where it is used for growth promoting purposes [10].

In humans, stanozolol is mainly metabolized by undergoing hydroxylation to form mono- and di-hydroxylated metabolites. The majority of these are excreted in urine in the form of conjugates. Less than 5% are excreted as non-conjugated fractions [10]. According to WADA, doping with stanozolol is confirmed if the urinary concentration of its major metabolite, 3-hydroxystanozolol exceeds 2 ng/mL [11]. Unlike testosterone, the synthetic stanozolol and/or its main metabolite should only appear in environmental waters if the former is used for veterinary purposes, taken under medical

* Correspondence: K0630928@kingston.ac.uk

¹School of Pharmacy and Chemistry, Kingston University, London, UK
Full list of author information is available at the end of the article

supervision or illegally by athletes for performance enhancement or if either one or both of these compounds are accidentally discharged into environmental waters. In previous studies, we reported the detection of stanozolol in hair samples collected from subjects living in Budapest [12,13]. For this reason, we initiated this study to explore possible environmental sources of steroid contamination.

The aim of this study was to develop a methodology for the detection of stanozolol in aqueous matrices. To achieve this, liquid - liquid extraction (LLE) was employed for purification and concentration followed by direct determination using LC-MS/MS. Extraction recovery was evaluated for aqueous matrices spiked with stanozolol at pg/mL levels.

Experimental

Reagents and chemicals

Stanozolol and stanozolol D3 (internal standard) were obtained from LGC standards (Teddington, London, UK). Pentane, deionised water, formic acid, and acetonitrile were obtained from Sigma Aldrich (Poole, Dorset, UK). All chemicals and reagents were of HPLC grade. Environmental water samples were obtained from Budapest (Hungary) and collected from the River Danube and an urban tap (drinking water) in clean, amber bottles. Water samples were collected periodically from December 2009 to November 2010. Samples from Lake Balaton and spring water (Rózsika forrás, Solymár, near Budapest) were also collected for comparison. Some commonly-consumed, bottled non-carbonated, natural mineral water samples were purchased from local supermarkets. The majority of the analysed, commercially available, bottled natural mineral waters are recognised by the European Union [14]. All water samples were stored at -20°C and protected from light prior to analysis.

Extraction procedure

Liquid-liquid extraction (LLE) using pentane was employed for the extraction of stanozolol from water samples. Suspended particles were not filtered from the river water so that the drug adsorbed on them could also be extracted efficiently. A 5 mL aliquot of each water sample was spiked with stanozolol D3 (internal standard, 50 µL of 10 ng/mL) [13] followed by the addition of 3 mL pentane. The contents were vortex mixed vigorously for 10 seconds followed by centrifugation at 3500 × g at ambient temperature for 5 minutes. The pentane layer was separated and collected in a silanized glass tube. To ensure good recovery, the extraction procedure was performed twice. Both organic fractions were pooled and dried by evaporation at 45 °C under a gentle stream of nitrogen gas. The dried residue was

then reconstituted with 50 µL acetonitrile. A 5 µL aliquot of the reconstituted solution was injected into the LC-MS/MS system for analysis.

Instrumentation

The LC-MS/MS system consisted of an Accela LC system (Thermo Scientific, UK) coupled to a TSQ Quantum triple quadrupole mass spectrometer (Thermo electron, UK) without a flow splitter. The LC system was comprised of a quaternary pump, automatic solvent degasser, column heater and an auto-sampler equipped with tray chiller. Chromatographic separation was obtained on an Agilent Zorbax SB-C18 column (2.1 mm × 50 mm, 1.8 µm) maintained at 60 °C. Water and acetonitrile both containing 0.1% formic acid were used as mobile phase solvents. The total flow rate through the column was 100 µL/minute. The gradient flow composition is shown in Table 1.

The mass spectrometer was equipped with an electrospray ionization (ESI) source operated in positive ion mode. The capillary temperature was maintained at 350 °C. An ion spray voltage of 4000 V was essential for optimum ionization of stanozolol and stanozolol D3 (internal standard). The protonated molecules, $[M+H]^+$, of stanozolol (m/z 329.2) and stanozolol D3 (m/z 332.2), were used as precursor ions for collision induced dissociation (CID) for MS-MS analysis. Selective reaction monitoring (SRM) was used to monitor the precursor ions and diagnostic product ions for unambiguous quantification of stanozolol. The collision energies and SRM, m/z transitions for stanozolol and internal standard (I.S.) are shown in Table 2.

The Thermo Scientific Xcalibur software (version 2.1) was used to control the LC system and mass spectrometer. Data analysis and assay performance was also evaluated using the same software. The performance of the analytical method was validated for the following set of parameters: linearity, specificity, accuracy, lower limit of detection (LLOD), lower limit of quantification (LLOQ), inter-day precision and intra-day precision. Calibration samples and quality control samples at low, medium and high concentration levels were prepared by fortifying 5 mL HPLC grade water with known concentrations of stanozolol and I.S. followed by LLE and LC-

Table 1 LC mobile phase gradient composition

LC run time (minutes)	0.1% Formic acid in acetonitrile (%)	0.1% Formic acid in water (%)
0	50	50
4	100	0
6.5	100	0
7	50	50
10	50	50

Table 2 Retention times, SRM transitions and collision energies of stanozolol and stanozolol D3 (internal standard)

Analytes	Retention time (min)	Transition (m/z)	Collision energy (eV)
Stanozolol	3.58	329.2 → 81.2	42
		329.2 → 121.2	50
Stanozolol D3	3.56	332.2 → 81.2	42

MS/MS analysis. The analyte-to-internal standard ratio was calculated by dividing the area of analyte peak by the area of the I.S. peak.

A calibration curve was constructed by plotting the analyte-to-internal standard ratio versus the known concentration of stanozolol in each sample. Linear regression analysis using the least squares method was employed to evaluate the calibration curve of analyte as a function of its concentrations in water samples. The LLOQ or lowest point on the calibration curve was defined as the lowest concentration of analyte which could be quantified with a precision < 20% (CV). To determine the lower limit of detection (LLOD), a number of serial 1:2 dilutions were made from the low standard (LLOQ). The lowest concentration which gave a response equivalent to three times the background noise was considered as the LLOD. The accuracy and intra-day precision was assessed by injecting QC samples in replicates at 3 different concentrations. This was repeated on three consecutive days to evaluate the inter-day precision of the assay. The average extraction recovery for the analyte was determined by comparing the analyte to internal standard peak area ratio obtained after extracting negative control water samples fortified with stanozolol at a final concentration of 2 pg/mL in presence of I.S with the un-extracted standard working solutions at the same concentrations. The matrix effects were assessed by comparing the responses of analyte and I.S. obtained from the extracted blank water samples (HPLC grade, tap water and river water) spiked with known concentrations of stanozolol and stanozolol D3 after extraction to those obtained from neat standard solution at the same final concentrations. Validation results are shown in Table 3.

Results and discussion

Method validation

Stanozolol was unambiguously analysed on the basis of its SRM transition and retention time (Figures 1 and 2) via the method proposed and validated herein. Regression analysis indicated that the assay showed excellent linearity within the quantification range of 0.5 to 200 pg/mL water for stanozolol. The LLOQ for stanozolol was found to be 0.5 pg/mL. The correlation coefficients were found to be greater than 0.996 during the method validation procedure. Under the optimized LC-MS/MS conditions, the assay was capable of detecting (LLOD) stanozolol, without any interference, at a concentration as low as 0.25 pg/mL water when 5 mL water was processed. The analytical characteristics of this method including accuracy, linearity, LLOD, LLOQ, inter-day precision, intra-day precision and extraction recoveries from HPLC grade, river and tap water are summarized in Table 3. The relative standard deviation (RSD) was used to assess method precision and it indicated good reproducibility.

Matrix effects in river water led to a reduction in peak areas of stanozolol and stanozolol D3 by 22.3% and 18.4%, respectively. Comparatively, tap water and HPLC water showed lesser matrix effects. The reduction in peak areas was possibly attributed to ion suppression in the ESI source. However, after internal standard correction, the matrix effects in all three types of water samples were comparable and in the range 95.4-97.3% as shown in Table 4. Thus, stanozolol D3 was used as an internal standard to: i) compensate for matrix induced changes in ionization of analyte, ii) correct any loss of analyte during sample preparation, iii) compensate for any variations in the instrument response from injection to injection. The absolute extraction recoveries (with I.S. correction) in three water types; namely HPLC grade water, Danube river water and tap water were in the range 95.3% to 98.4%. The relative extraction recoveries (with I.S. correction) in all three water types were found to be in the range 94.2 to 95.5% for stanozolol as shown in Table 5. This indicated that the method is capable of detecting stanozolol in different types of aqueous matrix when only 5 mL water was processed. The analytical prerequisites for efficient detection of stanozolol at low

Table 3 Summary of assay validation results for stanozolol

Analytes	Linear range (pg/mL)	Concentration (pg/mL)	Precision RSD (%)		Accuracy (%)
			Intraday N = 6+6+6	Interday N = 18+18+18	
Stanozolol	0.5 to 200	2	8.5	7.4	91.7
		16	3.7	8.8	100
		100	6.1	7.4	106.6




Figure 1 Chromatogram and mass spectrum of stanozolol spiked to Danube river water at a final concentration of 0.5 pg/mL.

levels in aqueous matrix were, purification of water samples using liquid-liquid extraction in presence of a deuterated internal standard followed by injecting only 5 μ L aliquot through the column combined with the optimized LC-MS/MS conditions employed for analysis.


Gas chromatography mass spectrometry (GC-MS) and high performance liquid chromatography (HPLC) coupled to fluorescence and UV detectors have been commonly employed to analyse steroids [15]. However, HPLC coupled to fluorescence detection involves laborious sample preparation steps and GC-MS requires a complicated sample derivatization step which makes the method more time consuming and expensive [15,16]. Hence, use of LC-MS/MS for analyzing steroids is a feasible approach as the sample preparation step involved is facile, economical and does not require any additional derivatization step. Compared to previous methods for detecting steroids in environmental waters [15,17-19], the major advantage of our method is that less volume (only 5 mL, opposed to up to 1000 mL) of water sample

is required for analysis. Another advantage includes the use of liquid-liquid extraction for purification of water samples, which is less time consuming and more economical in comparison to the solid phase extraction processes employed in previous studies [15,17-20].

Water analyses results

No stanozolol was detected in any of the fifteen bottled waters investigated. In three out of six samples from the Danube river, collected since December '09, stanozolol was detected with levels up to 1.82 pg/mL. In contrast, only one sample of urban tap drinking water from Budapest city was found to contain stanozolol at a concentration of 1.19 pg/mL. The results for stanozolol analysis in different water samples are shown in Table 6.

The possible sources of stanozolol entering the river are unknown, but may be from human or animal consumption and excretion of un-metabolized drug or due to accidental discharge of the parent compound. It should be noted that stanozolol was only found once in



tap water and that this level does not present a threat to health based on recommended intake levels. Water samples from river and tap were collected periodically until November and stanozolol concentrations were found to be reducing over time as shown in Table 5. The possible reasons for a gradual reduction in concentration could

be due to: i) variations in rates of contamination, ii) dilution of river water due to rise in water levels, (see Additional file 1), iii) degradation of the steroid in the river water due to other constituents in the river or photolysis, or deposition in the sediment.

The pH values of all the river and tap water samples collected were found to be in the neutral range. The pH

Table 4 Matrix effect results for stanozolol and stanozolol D3 in HPLC water, tap water and river water

Matrix	ME ¹ (%)		ME ² (%)
	Stanozolol	Stanozolol D3 (I.S.)	
HPLC water (N = 6)	95.9	98.7	97.3
Tap water (N = 6)	88.8	92.3	96.2
River water (N = 6)	77.7	81.6	95.4

ME¹ is matrix effect expressed as the ratio of mean peak area of analyte spiked postextraction to the mean peak area of the same analyte standard multiplied by 100. A value less than 100 indicates ion suppression. ME² is matrix effect corrected with internal standard.

Table 5 Extraction recovery of stanozolol (I.S. corrected) at 2 pg/mL

Matrix	Absolute extraction recovery (%)	Relative extraction recovery (%)
HPLC water (N = 6)	97.2	95.5
Tap water (N = 6)	98.4	94.5
River water (N = 6)	95.3	94.2

Table 6 Determination of stanozolol in environmental and domestic water samples

Environmental water sample (N = 3)	Average concentration pg/mL					
	31 st December 2009	18 th April 2010	21 th July 2010	01 st September 2010	24 th October 2010	05 th November 2010
River Danube	1.82 ± 0.19	0.71 ± 0.06	0.54 ± 0.03	ND	ND	ND
Budapest Tap	1.19 ± 0.03	0.31 (BLQ)	ND	ND	ND	ND
Lake Balaton	-	ND	-	-	-	-
Spring 'Rózsika'	-	ND	-	-	-	-

BLQ means below limit of quantification

ND means not detectable

values of bottled water analysed are summarized in Additional file 2. Stanozolol being basic in nature due to the presence of a pyrazole ring is found to be stable in neutral to slightly basic pH. Further investigation needs to be carried out for determining the source of stanozolol and reasons for gradual decrease in its concentration.

In recent years, numerous reports on steroids found in environmental waters have appeared. Stanozolol has been detected (qualitatively) in sludge samples collected from Huiyang and Meihu waste water treatment plants [17]. Chang *et al.* have also reported the presence of stanozolol in Beijing influent waste water at a concentration of *ca.* 0.54 pg/mL [18]. Recently, Tölgyesi *et al.* have reported the presence of the steroids cortisol, dexamethasone, flumethasone, prednisolone and epitestosterone in Danube river water [15], but their selection of analytes did not include stanozolol.

Our results indicate that stanozolol was present in the River Danube and Budapest tap water in the month of December 2009, when the water level in the river was low (Additional file 2). The National Health Service (NHS) recommends a minimum water intake of 1.2 litres every day [21]. Hence, individuals drinking stanozolol contaminated urban tap water (1.19 pg/mL) will involuntarily consume approximately 1.43 ng stanozolol per day. Since the effective doses of stanozolol for men and women are 50-100 mgs/day and 2.5-10 mgs/day respectively [22], such low levels detected in drinking water may not cause significant harm to the general public, especially as they were found only at one time point. In addition, a new biological sewage treatment plant opened in July 2010 in Budapest in order to treat most of the water supplied to the city (in contrast to only 30-40% water being treated in the past). This major environmental protection investment will potentially contribute to a further decrease in levels of stanozolol compared to those we previously observed. Future studies, sampling from various river and tap water sites should, in due course, be able to provide evidence for this.

Conclusions

In conclusion, a rapid, highly sensitive, robust and reproducible method has been developed to detect stanozolol in different types of water samples. The assay is capable of detecting stanozolol at a concentration as low as 0.25 pg/mL water when only 5 mL water is processed. The performance of this method gives acceptable relative recoveries for stanozolol river and tap water samples. The method can be extended to detect other chemicals and pharmaceutical drugs which may be hazardous to human health and environment.

Additional material

Additional file 1: Danube water level. The supporting document reports the water level, volume, and temperature of River Danube from December 2009 to November 2010.

Additional file 2: Details of bottled drinking water analysed. The supporting document reports the pH, EU recognition and origin of the bottled natural mineral water analysed.

Acknowledgements

The authors thank Julian Swinden and Iltaf Shah for technical advice and help; IP and FP for sample collection. The photos were taken by FP and ZsB.

Author details

¹School of Pharmacy and Chemistry, Kingston University, London, UK.

²School of Life Sciences, Kingston University, London, UK.

Authors' contributions

DPN initiated and all authors designed the study. The extraction and method developments were conducted by NIKD who prepared the draft paper. All authors contributed to data analyses and to finalizing the manuscript. All authors have read and approved the final version.

Competing interests

The authors declare that they have no competing interests.

Received: 17 June 2011 Accepted: 14 October 2011

Published: 14 October 2011

References

1. Rodriguez-Mozaz S, Weinberg S: Meeting report: pharmaceuticals in water—An interdisciplinary approach to a public health challenge. *Environ Health Perspect* 2010, **118**(7):1010-1020.

2. Costanzo S, Murby J, Bates J: **Ecosystem response to antibiotics entering the aquatic environment.** *Mar Pollut Bull* 2005, **51**:218-223.
3. Ternes TA: **Occurrence of drugs in German sewage treatment plants and rivers.** *Water Res* 1998, **32**:3245-3268.
4. Ye Z, Weinberg HS, Meyer MT: **Trace analysis of trimethoprim and sulfonamide, macrolide, quinolone, and tetracycline antibiotics in chlorinated drinking water using liquid chromatography electrospray tandem mass spectrometry.** *Anal Chem* 2007, **79**:1135-1144.
5. Heberer T: **Occurrence, fate, and removal of pharmaceutical residues in the aquatic environment: a review of recent research data.** *Toxicol Lett* 2002, **131**:5-17.
6. Glassmeyer S, Koplín D, Furlong E, Focazio M: **Environmental presence and persistence of pharmaceuticals: an overview.** In *Fate of Pharmaceuticals in the Environment and in Water Treatment Systems*. Edited by: Aga DS. Boca Raton, FL: CRC Press, Taylor and Francis Books; 2008:3-51.
7. Daughton CG, Ternes TA: **Pharmaceuticals and personal care products in the environment: agents of subtle change?** *Environ Health Perspect* 1999, **107**(6):907-938.
8. World Anti-Doping Agency: **The 2011 Prohibited List.**[http://www.wada-ama.org/Documents/World_Anti-Doping_Program/WADP-Prohibited-list/To_be_effective/WADA_Prohibited_List_2011_EN.pdf], [accessed on 11.06.2011].
9. World Anti-Doping Agency: **Laboratory statistics.**[http://www.wada-ama.org/rtecontent/document/WADA_2008_LaboratoryStatisticsReport_Final.pdf], [accessed on 09.06.2011].
10. Poelmans S, Wasch KD, De Brabander HF, Van De Wiele M, Courtheyn D: **Analytical possibilities for the detection of stanozolol and its metabolites.** *Anal Chim Acta* 2002, **473**:39-47.
11. World Anti-Doping Agency: **Technical Document - TD2010MRPL.**[http://www.wada-ama.org/Documents/World_Anti-Doping_Program/WADP-IS-Laboratories/WADA_TD2010MRPLv1.0_Minimum%20Required%20Performance%20Levels_Sept%2001%202010_EN.pdf], [accessed on 10.06.2011].
12. Petróczy A, Aidman EV, Hussain I, Deshmukh N, Nepusz T, Uvacsek M, Tóth M, Barker J, Naughton DP: **Virtue or Pretense? Looking behind Self-Declared Innocence in Doping.** *PLoS One* 2010, **5**(5):11.
13. Deshmukh N, Hussain I, Barker J, Petróczy A, Naughton DP: **Analysis of anabolic steroids in human hair using LC-MS/MS.** *Steroids* 2010, **75**(10):710-714.
14. **List of natural mineral waters recognised by member states.** [http://ec.europa.eu/food/food/labellingnutrition/water/mw_eulist_en.pdf], [accessed on 09.06.2011].
15. Tölgyesi A, Verebey Z, Sharma VK, Kovacsics L, Fekete J: **Simultaneous determination of corticosteroids, androgens, and progesterone in river water by liquid chromatography-tandem mass spectrometry.** *Chemosphere* 2010, **78**:972-979.
16. Kushnir MM, Rockwood AL, Roberts WL, Yue B, Bergquist J, Meikle AW: **Liquid chromatography tandem mass spectrometry for analysis of steroids in clinical laboratories.** *Clin Biochem* 2011, **45**(1):77-88.
17. Liu S, Ying GG, Zhao JL, Chen F, Yang B, Zhou LJ, Lai HJ: **Trace analysis of 28 steroids in surface water, wastewater and sludge samples by rapid resolution liquid chromatography-electrospray ionization tandem mass spectrometry.** *J Chromatogr A* 2011, **1218**(10):1367-1378.
18. Chang H, Wan Y, Wu S, Fan Z, Hu J: **Occurrence of androgens and progestogens in wastewater treatment plants and receiving river waters: Comparison to estrogens.** *Water Res* 2011, **45**(2):732-740.
19. Chang H, Wu S, Hu J, Asami M, Kunikane S: **Trace analysis of androgens and progestogens in environmental waters by ultra-performance liquid chromatography-electrospray tandem mass spectrometry.** *J Chromatogr A* 2008, **1195**:44-51.
20. Chang H, Wan Y, Hu J: **Determination and source apportionment of five classes of steroid hormones in urban rivers.** *Environ Sci Technol* 2009, **43**:7691-7698.
21. NHS: **A balanced diet.**[<http://www.nhs.uk/Conditions/Diet/Pages/Fluids.aspx>], [accessed on 09.06.2011].
22. Steroid: **Winstrol.**[<http://www.steroid.com/Winstrol.php>], [accessed on 09.06.2011].

doi:10.1186/1752-153X-5-63

Cite this article as: Deshmukh *et al.*: Detection of stanozolol in environmental waters using liquid chromatography tandem mass spectrometry. *Chemistry Central Journal* 2011 **5**:63.

Publish with **ChemistryCentral** and every scientist can read your work free of charge

“Open access provides opportunities to our colleagues in other parts of the globe, by allowing anyone to view the content free of charge.”

W. Jeffery Hurst, The Hershey Company.

- available free of charge to the entire scientific community
- peer reviewed and published immediately upon acceptance
- cited in PubMed and archived on PubMed Central
- yours — you keep the copyright

Submit your manuscript here:
<http://www.chemistrycentral.com/manuscript/>

